

**CAMBRIDGE INTERNATIONAL EXAMINATIONS**

Cambridge International Advanced Subsidiary and Advanced Level

## **MARK SCHEME for the May/June 2015 series**

### **9702 PHYSICS**

**9702/43**

Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2015 series for most Cambridge IGCSE<sup>®</sup>, Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is the registered trademark of Cambridge International Examinations.

Page 2	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

### Section A

- 1 (a) (gravitational) force proportional to product of masses and inversely proportional to square of separation  
reference to *either* point masses *or* particles *or* 'size' much less than separation
- M1  
A1 [2]
- (b) gravitational force provides/is the centripetal force  
 $GM_N m / r^2 = m r \omega^2$  (or  $m v^2 / r$ )  
 $2\pi / T$  (or  $v = 2\pi r / T$ ) leading to  $GM_N = 4\pi^2 r^3 / T^2$
- B1  
M1  
A1 [3]
- (c)  $M_N / M_U = (3.55 / 5.83)^3 \times (13.5 / 5.9)^2$   
 $x^3$  factor correct  
 $T^2$  factor correct  
ratio = 1.18 (allow 1.2)
- C1  
C1  
A1
- alternative method:* mass of Neptune =  $1.019 \times 10^{26}$  kg  
mass of Uranus =  $8.621 \times 10^{25}$  kg  
ratio = 1.18
- (C1)  
(C1)  
(A1) [3]
- 2 (a) (sum of) potential energy and kinetic energy of molecules/atoms/particles  
mention of random motion/distribution
- M1  
A1 [2]
- (b) (i)  $pV = nRT$   
*either* at A,  $1.2 \times 10^5 \times 4.0 \times 10^{-3} = n \times 8.31 \times 290$   
*or* at B,  $3.6 \times 10^5 \times 4.0 \times 10^{-3} = n \times 8.31 \times 870$   
 $n = 0.20$  mol
- C1  
A1 [2]
- (ii)  $1.2 \times 10^5 \times 7.75 \times 10^{-3} = 0.20 \times 8.31 \times T$  *or*  $T = (7.75 / 4.0) \times 290$   
 $T = 560$  K  
(Allow tolerance from graph:  $7.7-7.8 \times 10^{-3}$  m<sup>3</sup>)
- C1  
A1 [2]
- (c) temperature changes/decreases so internal energy changes/decreases  
volume changes (at constant pressure) so work is done
- B1  
B1 [2]
- 3 (a) (numerically equal to) quantity of (thermal) energy/heat to change state/phase of unit mass  
at constant temperature  
(allow 1/2 for definition restricted to fusion or vaporisation)
- M1  
A1 [2]
- (b) (i) at 70 W, mass s<sup>-1</sup> = 0.26 g s<sup>-1</sup>  
at 110 W, mass s<sup>-1</sup> = 0.38 g s<sup>-1</sup>
- A1  
A1 [2]



Page 4	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

- (b) (i) out of (plane of) paper/page (*not* “upwards”) B1 [1]
- (ii)  $B = mv/qr$  C1  
 $= (3.32 \times 10^{-26} \times 7.6 \times 10^4)/(1.6 \times 10^{-19} \times 6.1 \times 10^{-2})$  C1  
 $= 0.26 \text{ T}$  A1 [3]
- (c) sketch: semicircle with diameter < 12.2 cm B1 [1]
- 7 (a) can change (output) voltage efficiently *or* to suit different consumers/appliances by using transformers B1  
B1 [2]
- (b) for same power, current is smaller B1
- less heating in cables/wires  
*or* thinner cables possible  
*or* less voltage loss in cables B1 [2]
- 8 (a) (i)  $p = h/\lambda$   
 $= (6.63 \times 10^{-34})/(6.50 \times 10^{-12})$  C1  
 $= 1.02 \times 10^{-22} \text{ N s}$  A1 [2]
- (ii)  $E = hc/\lambda$  *or*  $E = pc$   
 $= (6.63 \times 10^{-34} \times 3.00 \times 10^8)/(6.50 \times 10^{-12})$  C1  
 $= 3.06 \times 10^{-14} \text{ J}$  A1 [2]
- (b) (i)  $0.34 \times 10^{-12} = (6.63 \times 10^{-34})/(9.11 \times 10^{-31} \times 3.0 \times 10^8) \times (1 - \cos \theta)$  C1  
 $\theta = 30.7^\circ$  A1 [2]
- (ii) deflected electron has energy M1  
this energy is derived from the incident photon A1  
deflected photon has less energy, longer wavelength (so  $\Delta\lambda$  always positive) B1 [3]
- 9 (a) nucleus/nuclei emits M1  
spontaneously/randomly A1  
 $\alpha$ -particles,  $\beta$ -particles,  $\gamma$ -ray photons A1 [3]
- (b) (i)  $N - \Delta N$  A1 [1]
- (ii)  $\Delta N/\Delta t$  A1 [1]
- (iii)  $\Delta N/N$  A1 [1]
- (iv)  $\Delta N/N\Delta t$  A1 [1]
- (c) graph: smooth curve in correct direction starting at (0,0) M1  
 $n$  at  $2t_{1/2}$  is 1.5 times that at  $t_{1/2}$  ( $\pm 2 \text{ mm}$ ) A1 [2]

Page 5	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

### Section B

- 10 (a) (i)** (potential =)  $1.2 / (1.2 + 4.2) \times 4.5 = +1.0\text{V}$  A1 [1]
- (ii)** (for  $V_{\text{IN}} > 1.0\text{V}$ )  $V^+ > V^-$  B1  
output (of op-amp) is +5 V or positive M1  
diode conducts giving +5 V across R or  $V_{\text{out}}$  is +5 V A1
- (for  $V_{\text{IN}} < 1.0\text{V}$ ) output of op-amp  $-5\text{V}$ /negative so diode does not conduct,  
giving  $V_{\text{out}} = 0$  or  $0\text{V}$  across R A1 [4]
- (b) (i)** square wave with maximum value +5 V and minimum value 0 M1  
vertical sides in correct positions and correct phase A1 [2]
- (ii)** re-shaping (digital) signals/regenerator (amplifier) B1 [1]
- 11 (a)** change/increase/decrease anode/tube voltage B1  
electrons striking anode have changed (kinetic) energy/speed B1  
X-ray/photons/beam have different wavelength/frequency B1 [3]
- (b) (i)**  $I = I_0 e^{-\mu x}$  B1 [1]
- (ii)** contrast is difference in degree of blackening (of regions of the image) B1  
 $\mu$  (very) similar so similar absorption of radiation (for same thickness) so little contrast A1 [2]
- 12 (a) (i)** loudspeaker/doorbell/telephone etc. B1 [1]
- (ii)** television set/audio amplifier etc. B1 [1]
- (iii)** satellite/satellite dish/mobile phone etc. B1 [1]
- (b)** e.g. lower attenuation/fewer repeaters  
more secure  
less prone to noise/interference  
physically smaller/less weight  
lower cost  
greater bandwidth  
*(any two sensible suggestions, 1 each)* B2 [2]
- (c) (i)** ratio =  $25 + (62 \times 0.21)$  C1  
= 38 dB A1 [2]
- (ii)** ratio/dB =  $10 \lg(P_2/P_1)$  C1  
 $38 = 10 \lg(P/\{9.2 \times 10^{-6}\})$
- $P = 58 \text{ mW}$  or  $5.8 \times 10^{-2} \text{ W}$  A1 [2]  
*(allow 1/2 for missing 10 in equation)*

Page 6	Mark Scheme	Syllabus	Paper
	Cambridge International AS/A Level – May/June 2015	9702	43

- 13 (a) (i) to align nuclei/protons  
to cause Larmor/precessional frequency to be in r.f. region
- B1  
B1 [2]
- (ii) Larmor/precessional frequency depends on (applied magnetic) field strength  
knowing field strength enables (region of precessing) nuclei to be located  
by knowing the frequency
- B1  
M1  
A1 [3]
- (b)  $E = 2.82 \times 10^{-26} \times B$   
 $6.63 \times 10^{-34} \times 42 \times 10^6 = 2.82 \times 10^{-26} \times B$
- C1
- $B = 0.99 \text{ T}$
- A1 [2]