

**UNIVERSITY OF CAMBRIDGE INTERNATIONAL EXAMINATIONS**

**GCE Advanced Subsidiary Level and GCE Advanced Level**

**MARK SCHEME for the May/June 2012 question paper  
for the guidance of teachers**

**9702 PHYSICS**

**9702/52**

Paper 5 (Planning, Analysis and Evaluation),  
maximum raw mark 30

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes must be read in conjunction with the question papers and the report on the examination.

- Cambridge will not enter into discussions or correspondence in connection with these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2012 question papers for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level syllabuses and some Ordinary Level syllabuses.

<b>Page 2</b>	<b>Mark Scheme: Teachers' version</b>	<b>Syllabus</b>	<b>Paper</b>
	<b>GCE AS/A LEVEL – May/June 2012</b>	<b>9702</b>	<b>52</b>

## 1 Planning (15 marks)

### Defining the problem (3 marks)

- P1  $v$  is the independent variable and  $\theta$  is the dependent variable or vary  $v$  and measure  $\theta$ . [1]
- P2 Keep the (shape and) size/volume/surface area/mass of balloon/helium constant  
Do not credit 'same balloon'. [1]
- P3 Keep the temperature (air/helium/balloon) constant. [1]

### Methods of data collection (5 marks)

- M1 Labelled diagram of apparatus: balloon, string fixed and method of producing wind.  
Method of producing wind to be approximately horizontal to balloon. [1]
- M2 Suspend mass from balloon. [1]
- M3 Method to change wind speed, e.g. change setting, variable power supply/resistor/change distance from fan. [1]
- M4 Method to measure wind speed, e.g. wind speed indicator/detector, anemometer [1]
- M5 Method to measure angle – use protractor or rule for measurements for trigonometry methods.  
This must be shown correctly on diagram or explained in text. [1]

### Method of analysis (2 marks)

- A1 Plot a graph of  $\tan \theta$  against  $1/v^2$ . [1]
- A2 Relationship valid if straight line through origin [1]

### Safety considerations (1 mark)

- S1 Avoid the moving blades of the fan (safety screen, switch off when changing experiment);  
goggles to avoid air stream into eye. [1]

### Additional detail (4 marks)

- D1/2/3/4 Relevant points might include [4]
- 1 Large wind speed to produce measurable deflection/large cross-sectional area of balloon.
  - 2 Additional detail on measuring angle e.g. use a large protractor, projection method.
  - 3  $\tan \theta = h/l$ .
  - 4 Measuring air speed at point where balloon is positioned.
  - 5 Adjust height of fan so that air flow is horizontally aligned to the balloon.
  - 6 Reason for adding mass to increase stability/deflection.
  - 7 Keep windows shut/air conditioning switched off/use of wind tunnel to avoid draughts.
  - 8 Wait for the balloon to become stable.

Do not allow vague computer methods.

**[Total: 15]**

Page 3	Mark Scheme: Teachers' version	Syllabus	Paper
	GCE AS/A LEVEL – May/June 2012	9702	52

## 2 Analysis, conclusions and evaluation (15 marks)

Part	Mark	Expected Answer	Additional Guidance
(a)	A1	Gradient = $\frac{1}{2} \sqrt{\frac{T}{\mu}}$	Allow equivalent, e.g. $\sqrt{\frac{T}{4\mu}}$
(b)	T1	$1/L / \text{m}^{-1}$ or $(1/L) / \text{m}^{-1}$	Allow $1/L (\text{m}^{-1})$ , $1/L / 1/\text{m}$ , $1/L (1/\text{m})$
	T2	1.83 or 1.835 2.08 or 2.083 2.35 or 2.353 2.50 or 2.500 2.82 or 2.817 3.13 or 3.125	Values must correspond to table. A mixture of 3 s.f. and 4 s.f. is allowed
	U1	From $\pm 0.01$ or $\pm 0.02$ , to $\pm 0.05$	Allow more than one significant figure.
(c) (i)	G1	Six points plotted correctly	Must be within half a small square. Penalise 'blobs' (more than half a small square). Ecf allowed from table.
	U2	All Error bars in $1/L/\text{m}^{-1}$ plotted correctly.	Check second and last point for accuracy. Must be accurate within half a small square.
(ii)	G2	Line of best fit	If points are plotted correctly then lower end of line should pass between (1.8, 250) and (1.8, 254) <b>and</b> upper end of line should pass between (3.18, 450) and (3.2, 448). Allow ecf from points plotted incorrectly – examiner judgement.
	G3	Worst acceptable straight line. Steepest or shallowest possible line that passes through <u>all</u> the error bars.	Line should be clearly labelled or dashed. Should pass from left of top error bar to right of bottom error bar <b>or</b> right of top error bar to left of bottom error bar. Mark scored only if all error bars are plotted.
(iii)	C1	Gradient of best fit line	The triangle used should be at least half the length of the drawn line. Check the read offs. Work to half a small square. Do not penalise POT. (Should be about 140)
	U3	Uncertainty in gradient	Method of determining absolute uncertainty Difference in worst gradient and gradient.
(d) (i)	C2	Value of $\mu$ using gradient	$\mu = 7.5/\text{gradient}^2$ Gradient must be used. (Should be about 0.00037 or $3.7 \times 10^{-4}$ )
	C3	$\text{kg m}^{-1}$ or $\text{N Hz}^{-2} \text{m}^{-2}$	Allow other correct units e.g. $\text{N s}^2 \text{m}^{-2}$ or $\text{Pa s}^2$ or $\text{N} (\text{Hz m})^{-2}$
(ii)	U4	10% + 2 × percentage uncertainty in gradient	Check working. Must be larger than 10%.

<b>Page 4</b>	<b>Mark Scheme: Teachers' version</b>	<b>Syllabus</b>	<b>Paper</b>
	<b>GCE AS/A LEVEL – May/June 2012</b>	<b>9702</b>	<b>52</b>

<b>(e)</b>	C4	$r$ given to 2 or 3 s.f. <u>and</u> in the range $1.15 \times 10^{-4}$ to $1.18 \times 10^{-4}$	Allow 1.2 to 2 s.f. Penalise 1 s.f. or >3 s.f.
	U5	<b>(d)(ii)</b> / 2	Check working if not <b>(d)(ii)</b> / 2

[Total: 15]

### Uncertainties in Question 2

- (c) (iii)** Gradient [U3]  
 Uncertainty = gradient of line of best fit – gradient of worst acceptable line  
 Uncertainty =  $\frac{1}{2}$  (steepest worst line gradient – shallowest worst line gradient)

- (d) (ii)** [U4]

$$\text{Percentage uncertainty} = 10 + 2 \frac{\Delta m}{m}$$

$$\text{Percentage uncertainty} = \frac{\frac{\max T}{4 \times \min m^2} - \mu}{\mu} \times 100$$

$$\text{Percentage uncertainty} = \frac{\frac{\min T}{4 \times \max m^2} - \mu}{\mu} \times 100$$

- (e) (ii)** [U5]

$$\text{Percentage uncertainty} = \frac{\max r - r}{r} \times 100$$

$$\text{Percentage uncertainty} = \frac{\min r - r}{r} \times 100$$