



Mark Scheme (Results)

October 2020

Pearson Edexcel GCE Advanced Level
In Mathematics (9MA0)
Paper 32: Mechanics

Edexcel and BTEC Qualifications

Edexcel and BTEC qualifications are awarded by Pearson, the UK's largest awarding body. We provide a wide range of qualifications including academic, vocational, occupational and specific programmes for employers. For further information visit our qualifications websites at www.edexcel.com or www.btec.co.uk. Alternatively, you can get in touch with us using the details on our contact us page at www.edexcel.com/contactus.

Pearson: helping people progress, everywhere

Pearson aspires to be the world's leading learning company. Our aim is to help everyone progress in their lives through education. We believe in every kind of learning, for all kinds of people, wherever they are in the world. We've been involved in education for over 150 years, and by working across 70 countries, in 100 languages, we have built an international reputation for our commitment to high standards and raising achievement through innovation in education. Find out more about how we can help you and your students at: www.pearson.com/uk

Autumn 2020

Publications Code 9MA0_32_2010_MS

All the material in this publication is copyright

© Pearson Education Ltd 2020

General Marking Guidance

- All candidates must receive the same treatment. Examiners must mark the first candidate in exactly the same way as they mark the last.
- Mark schemes should be applied positively. Candidates must be rewarded for what they have shown they can do rather than penalised for omissions.
- Examiners should mark according to the mark scheme not according to their perception of where the grade boundaries may lie.
- There is no ceiling on achievement. All marks on the mark scheme should be used appropriately.
- All the marks on the mark scheme are designed to be awarded. Examiners should always award full marks if deserved, i.e. if the answer matches the mark scheme. Examiners should also be prepared to award zero marks if the candidate's response is not worthy of credit according to the mark scheme.
- Where some judgement is required, mark schemes will provide the principles by which marks will be awarded and exemplification may be limited.
- When examiners are in doubt regarding the application of the mark scheme to a candidate's response, the team leader must be consulted.
- Crossed out work should be marked UNLESS the candidate has replaced it with an alternative response.

EDEXCEL GCE MATHEMATICS
General Instructions for Marking

1. The total number of marks for the paper is 50.
2. The Edexcel Mathematics mark schemes use the following types of marks:
 - **M** marks: method marks are awarded for 'knowing a method and attempting to apply it', unless otherwise indicated.
 - **A** marks: Accuracy marks can only be awarded if the relevant method (M) marks have been earned.
 - **B** marks are unconditional accuracy marks (independent of M marks)
 - Marks should not be subdivided.

3. Abbreviations

These are some of the traditional marking abbreviations that will appear in the mark schemes.

- bod – benefit of doubt
 - ft – follow through
 - the symbol \checkmark will be used for correct ft
 - cao – correct answer only
 - cso - correct solution only. There must be no errors in this part of the question to obtain this mark
 - isw – ignore subsequent working
 - awrt – answers which round to
 - SC: special case
 - oe – or equivalent (and appropriate)
 - dep – dependent
 - indep – independent
 - dp decimal places
 - sf significant figures
 - * The answer is printed on the paper
 - \square The second mark is dependent on gaining the first mark
4. For misreading which does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, in that part of the question affected.
 5. Where a candidate has made multiple responses and indicates which response they wish to submit, examiners should mark this response.
If there are several attempts at a question which have not been crossed out, examiners should mark the final answer which is the answer that is the most complete.
 6. Ignore wrong working or incorrect statements following a correct answer.
 7. Mark schemes will firstly show the solution judged to be the most common response expected from candidates. Where appropriate, alternatives answers are provided in the notes. If examiners are not sure if an answer is acceptable, they will check the mark scheme to see if an alternative answer is given for the method used.

General Principles for Mechanics Marking

(But note that specific mark schemes may sometimes override these general principles)

- Rules for M marks: correct no. of terms; dimensionally correct; all terms that need resolving (i.e. multiplied by cos or sin) are resolved.
- Omission or extra g in a resolution is an accuracy error not method error.
- Omission of mass from a resolution is a method error.
- Omission of a length from a moments equation is a method error.
- Omission of units or incorrect units is not (usually) counted as an accuracy error.
- DM indicates a dependent method mark i.e. one that can only be awarded if a previous specified method mark has been awarded.
- Any numerical answer which comes from use of $g = 9.8$ should be given to 2 or 3 SF.
- Use of $g = 9.81$ should be penalised once per (complete) question.

N.B. Over-accuracy or under-accuracy of correct answers should only be penalised *once* per complete question. However, premature approximation should be penalised every time it occurs.

- Marks must be entered in the same order as they appear on the mark scheme.
- In all cases, if the candidate clearly labels their working under a particular part of a question i.e. (a) or (b) or (c),.....then that working can only score marks for that part of the question.
- Accept column vectors in all cases.
- Misreads – if a misread does not alter the character of a question or materially simplify it, deduct two from any A or B marks gained, bearing in mind that after a misread, the subsequent A marks affected are treated as A ft
- Mechanics Abbreviations

M(A) Taking moments about A.

N2L Newton's Second Law (Equation of Motion)

NEL Newton's Experimental Law (Newton's Law of Impact)

HL Hooke's Law

SHM Simple harmonic motion

PCLM Principle of conservation of linear momentum

RHS, LHS Right hand side, left hand side.

Question	Scheme		Marks	AOs
1.(a)	Resolve perpendicular to the plane		M1	3.4
	$R = mg \cos \alpha = \frac{4}{5}mg$		A1	1.1b
			(2)	
1(b)	Resolve parallel to the plane or horizontally or vertically		M1	3.4
	$F = mg \sin \alpha$ or $R \sin \alpha = F \cos \alpha$		A1	1.1b
	Use $F = \mu R$ and solve for μ		M1	2.1
	$\mu = \frac{3}{4}$ *		A1*	2.2a
			(4)	
1(c)	The forces acting on Q will still balance as the m 's cancel oe Other possibilities: e.g. the <u>friction</u> will increase <u>in the same proportion</u> as <u>the weight component or force down the plane</u> . The <u>force pulling the brick down the plane</u> increases <u>by the same amount</u> as the <u>friction</u> oe This mark can be scored if they do the calculation.		B1	2.4
			(1)	
1(d)	Brick Q slides down the plane with constant speed.		B1	2.4
	No resultant force down the plane (so no acceleration) oe		B1	2.4
	These marks can be scored if they do the calculation.		(2)	
(9 marks)				
Notes:				
1a	M1	Correct no. of terms, condone sin/cos confusion		
	A1	cao with no wrong working seen. $mg \cos 36.86$ is A0		
1b	M1	Correct no. of terms, condone sin/cos confusion		
	A1	Correct equation		
	M1	Must use $F = \mu R$ (not merely state it) to obtain a numerical value for μ . This is an independent M mark.		
	A1*	Given answer correctly obtained		
1c	B1	Must have the 3 underlined phrases/word oe		
1d	B1	Must say constant speed.		
	B1	Any appropriate equivalent statement		

Question	Scheme	Marks	AOs
2(a)	Use of $\mathbf{v} = \mathbf{u} + \mathbf{a}t$ or integrate to give: $\mathbf{v} = (-2\mathbf{i} + 2\mathbf{j}) + 2(4\mathbf{i} - 5\mathbf{j})$	M1	3.1a
	$(6\mathbf{i} - 8\mathbf{j}) (\text{m s}^{-1})$	A1	1.1b
		(2)	
2(b)	Solve problem through use of $\mathbf{r} = \mathbf{u}t + \frac{1}{2}\mathbf{a}t^2$ or integration (M0 if $\mathbf{u} = \mathbf{0}$) Or any other complete method e.g use $\mathbf{v} = \mathbf{u} + \mathbf{a}T$ and $\mathbf{r} = \frac{(\mathbf{u} + \mathbf{v})T}{2}$:	M1	3.1a
	$-4.5\mathbf{j} = 2t\mathbf{j} - \frac{1}{2}t^2 5\mathbf{j}$ (\mathbf{j} terms only)	A1	1.1b
	The first two marks could be implied if they go straight to an algebraic equation.		
	Attempt to equate \mathbf{j} components to give equation in T only $(-4.5 = 2T - \frac{5}{2}T^2)$	M1	2.1
	$T = 1.8$	A1	1.1b
		(4)	
2(c)	Solve problem by substituting <u>their</u> T value (M0 if $T < 0$) into the \mathbf{i} component equation to give an equation in λ only: $\lambda = -2T + \frac{1}{2}T^2 \times 4$	M1	3.1a
	$\lambda = 2.9$ or 2.88 or $\frac{72}{25}$ oe	A1	1.1b
		(2)	

Notes: Accept column vectors throughout

(8 marks)

2a	M1	For any complete method to give a \mathbf{v} expression with correct no. of terms with $t = 2$ used, so if integrating, must see the initial velocity as the constant. Allow sign errors.
	A1	Caosw if they go on to find the speed.
2b	M1	For any complete method to give a vector expression for \mathbf{j} component of displacement in t (or T) only, using $\mathbf{a} = (4\mathbf{i} - 5\mathbf{j})$, so if integrating, RHS of equation must have the correct structure. Allow sign errors.
	A1	Correct \mathbf{j} vector equation in t or T . Ignore \mathbf{i} terms.
	M1	Must have earned 1 st M mark.

		Equate \mathbf{j} components to give equation in T (allow t) only (no \mathbf{j} 's) which has come from a displacement. Equation must be a 3 term quadratic in T .
	A1	cao
2c	M1	Must have earned 1 st M mark in (b) Complete method - must have an equation in λ only (no \mathbf{i} 's) which has come from an appropriate displacement.. (e.g M0 if $\mathbf{a} = \mathbf{0}$ has been used) Expression for λ must be a quadratic in T
	A1	cao

Question	Scheme		Marks	AOs
3(i)(a)	Integrate a wrt t to obtain velocity		M1	3.4
	$\mathbf{v} = (t - 2t^2)\mathbf{i} + \left(3t - \frac{1}{3}t^3\right)\mathbf{j} (+\mathbf{C})$		A1	1.1b
	$8\mathbf{i} - \frac{28}{3}\mathbf{j} \text{ (m s}^{-1}\text{)}$		A1	1.1b
			(3)	
3(i)(b)	Equate i component of v to zero		M1	3.1a
	$t - 2t^2 + 36 = 0$		A1ft	1.1b
	$t = 4.5$ (ignore an incorrect second solution)		A1	1.1b
			(3)	
3(ii)	Differentiate r wrt to t to obtain velocity		M1	3.4
	$\mathbf{v} = (2t - 1)\mathbf{i} + 3\mathbf{j}$		A1	1.1b
	Use magnitude to give an equation in t only		M1	2.1
	$(2t - 1)^2 + 3^2 = 5^2$		A1	1.1b
	Solve problem by solving this equation for t		M1	3.1a
	$t = 2.5$		A1	1.1b
			(6)	
(12 marks)				
Notes: Accept column vectors throughout				
3(i)(a)	M1	At least 3 terms with powers increasing by 1 (but M0 if clearly just multiplying by t)		
	A1	Correct expression		
	A1	Accept $8\mathbf{i} - 9.3\mathbf{j}$ or better. Isw if speed found.		
3(i)(b)	M1	Must have an equation in t only (Must have integrated to find a velocity vector)		
	A1ft	Correct equation follow through on their v but must be a 3 term quadratic		
	A1	cao		
3(ii)	M1	At least 2 terms with powers decreasing by 1 (but M0 if clearly just dividing by t)		
	A1	Correct expression		
	M1	Use magnitude to give an equation in t only, must have differentiated to find a velocity (M0 if they use $\sqrt{x^2 - y^2}$)		

	A1	Correct equation $\sqrt{(2t-1)^2 + 3^2} = 5$
	M1	Solve a 3 term quadratic for t which has come from differentiating and using a magnitude. This M mark can be implied by a correct answer with no working.
	A1	2.5

Question	Scheme	Marks	AOs
4(a)	Take moments about A	M1	3.3
	$N \times \frac{4a}{\sin \alpha} = Mg \times 3a \cos \alpha$	A1	1.1b
	$\frac{9Mg}{25} *$	A1*	1.1b
		(3)	
4(b)	Resolve horizontally	M1	3.4
	$(\rightarrow) F = \frac{9Mg}{25} \sin \alpha$	A1	1.1b
	Resolve vertically	M1	3.4
	$(\uparrow) R + \frac{9Mg}{25} \cos \alpha = Mg$	A1	1.1b
	Other possible equations: $(\nwarrow), R \cos \alpha + \frac{9Mg}{25} = Mg \cos \alpha + F \sin \alpha$ $(\nearrow), Mg \sin \alpha = F \cos \alpha + R \sin \alpha$ M(C), $Mg \cdot 2a \cos \alpha + F \cdot 5a \sin \alpha = R \cdot 5a \cos \alpha$ M(G), $\frac{9Mg}{25} \cdot 2a + F \cdot 3a \sin \alpha = R \cdot 3a \cos \alpha$ M(B), $Mg \cdot 3a \cos \alpha + F \cdot 6a \sin \alpha = R \cdot 6a \cos \alpha + \frac{9Mg}{25} a$ $(F = \frac{36Mg}{125}, R = \frac{98Mg}{125})$		
	$F = \mu R$ used	M1	3.4
	Eliminate R and F and solve for μ	M1	3.1b
	Alternative equations if they have at A: X horizontally and Y perpendicular to the rod. $(\nwarrow), Y + \frac{9Mg}{25} = Mg \cos \alpha + X \sin \alpha$ $(\nearrow), Mg \sin \alpha = X \cos \alpha$ $(\uparrow), \frac{9Mg}{25} \cos \alpha + Y \cos \alpha = Mg$ $(\rightarrow), Y \sin \alpha + \frac{9Mg}{25} \sin \alpha = X$		

		$M(C), Mg.2a \cos \alpha + X.5a \sin \alpha = Y.5a$ $M(G), \frac{9Mg}{25}.2a + X.3a \sin \alpha = Y.3a$ $M(B), Mg.3a \cos \alpha + X.6a \sin \alpha = Y.6a + \frac{9Mg}{25}a$ $(X = \frac{4Mg}{3}, Y = \frac{98Mg}{75})$ Then $F = \mu R$ becomes: $X - Y \sin \alpha = \mu Y \cos \alpha$ Eliminate X and Y and solve for μ	M1A1 M1A1		
		$\mu = \frac{18}{49}$ (0.3673.....accept 0.37 or better)		A1	2.2a
				(7)	
(10 marks)					
Notes:					
4a	M1	Correct no. of terms, dim correct, condone sin/cos confusion and sign errors for an equation in N and Mg only. For perp distance allow any of : $\frac{4a}{\sin \alpha}, \frac{4a}{\cos \alpha}, 5a$ but use of any of : $6a, 5a \sin \alpha, 4a \cos \alpha, \dots$ or anything involving $\tan \alpha$ is M0 Also M0 if no a 's in their first equation.			
	A1	Correct equation, trig does not need to be substituted			
	A1*	Given answer correctly obtained.			
4b	M1	Correct no. of terms, dim correct, condone sin/cos confusion and sign errors			
	A1	Correct equation, trig does not need to be substituted but N does.			
	M1	Correct no. of terms, dim correct, condone sin/cos confusion and sign errors			
	A1	Correct equation, trig does not need to be substituted but N does.			
		N.B. The above 4 marks are for any two equations, either resolutions or moments or one of each. Mark best two equations. Equations may appear in part (a) but must be used in (b) to earn marks.			
	M1	Must be used, e.g. seen on the diagram. i.e. M0 if merely quoting it. (M0 if $F = \mu \times \frac{9Mg}{25}$ used)			
	M1	Must have 3 equations (<u>and all 3 previous M marks</u>)			
	A1	Accept 0.37 or better			

Question	Scheme		Marks	AOs
5(a)	Using horizontal motion		M1	3.3
	$U \cos 45^\circ t = 100$		A1	1.1b
	Using vertical motion		M1	3.4
	$U \sin 45^\circ t - \frac{1}{2}gt^2 = -25$		A1	1.1b
	Solve problem by eliminating t and solving for U		M1	3.1b
	$U = 28^*$		A1*	1.1b
			(6)	
5(b)	Using vertical motion		M1	3.4
	$0^2 = (28 \sin 45^\circ)^2 - 2gh$		A1	1.1b
	Greatest height = 45 m		A1	1.1b
		(3)		
5(c)	New value > 28		B1	3.5a
			(1)	
5(d)	e.g. wind effects, more accurate value of g , spin of ball, include size of the ball, not model as a particle, shape of ball		B1	3.5c
			(1)	
(11 marks)				
Notes:				
5a	M1	Complete method to give equation in U and t only, condone sin/cos confusion and sign errors		
	A1	Correct equation		
	M1	Complete method to give equation in U and t only, condone sin/cos confusion and sign errors		
	A1	Correct equation (g does not need to be substituted)		
	M1	Must have earned the previous two M marks. Eliminate t and solve for U . N.B. They may solve for t first ($100 - \frac{1}{2}gt^2 = -25$) and then use it to find U .		
	A1*	Exact given answer correctly obtained with no wrong working (e.g. $g = 9.81$ used) or approximation seen.		
5b	M1	Complete method to give equation in h only (allow if U not substituted), condone sin/cos confusion and sign errors		

	A1	Correct equation (g does not need to be substituted) (A0 if U is used instead of 28)
	A1	cao
5c	B1	Clear statement
5d	B1	Penalise incorrect extras i.e. B0 if there are incorrect extras. The ground being horizontal, the cliff being vertical, .. are not part of the model so B0 Include weight/mass of the ball B0

Pearson Education Limited. Registered company number 872828
with its registered office at 80 Strand, London, WC2R 0RL, United Kingdom